

COMPACT SMOKING APPARATUS AND MANUFACTURE THEREOF

This application claims priority from U.S. provisional patent application 60/260,783 filed January 10, 2001.

BACKGROUND OF THE INVENTION

5 This invention relates to a smoking apparatus and, more particularly, to an apparatus which holds a smoking pipe and loose smoking material. The invention also relates to a milled wooden blank for use in manufacturing a smoking apparatus, and to a method for manufacturing a smoking apparatus.

10 There are many compact smoking systems in the prior art which are designed to help smokers reduce the amount of tobacco they smoke. Most of these systems have a base and a lid. The base generally has a receptacle for carrying loose smoking material and a pipe receptacle where a pipe is housed. The lid, in some fashion, covers openings to the receptacles in the base when closed, and exposes the receptacles in the base when the lid is in open position. The pipe housed in the pipe receptacle is upwardly projected above the top edge of the base by the means of a spring when the lid uncovers the pipe receptacle. The vast majority are made out of wood, and have a design that makes them difficult to manufacture.

15 U.S. Pat. Nos. 4,214,658 and 5,465,738 disclose smoking systems in which a pipe is moved into accessible position by means of a resilient element when its cover is slid to the side. U.S. Pat. No. 5,967,310 discloses a smoking system with a pivotably mounted lid. The configuration of these prior designs does not facilitate simple manufacture.

20 Prior smoking systems had designs which included contours such that the depth and/or width of the systems changed in the linear direction from the top of systems to the bottom of the systems, such that they could not be manufactured in a simple operation using a multiple-head

5 milling machine. For example, the lids in the slide-top
versions shown in 4,214,658 and 5,465,738 flared outwardly
from their top to their bottom. Other designs for pivot-top
designs are shown, for example, generally in FIGS. 24-29 of
10 the this application. With contours 26 and 27, these
designs have a depth, from the front of the device body 21
to the back of the device body, which is not constant from
the top of the device to the bottom. The contours 26 and 27
do not travel the entire length of the body. In particular,
15 the shape of the body of the device near the top, where the
contours 26 and 27 are, is not the same as the shape of the
body below this contour. This aspect makes manufacture more
difficult, and precludes simple manufacture using a
multiple-head wood milling machine. These machines mill the
same shape down the entire length of a piece of wood, and
thus do not produce the shape shown in these figures.
Additional wood shaping operations are required to produce
the final product including contours 26 and 27. Moreover,
20 sections 36 and 37 of the lid 22 (attached by fastener 28
seated in recess 10 at hole 25) must be machined into the
lid to expose the full diameter of the receptacle 23 and
receptacle 24 for pipe 15 when the lid is rotated, and
cannot be machined into the lid in the same multiple-head
milling operation which machines the body. These devices
25 are therefore more time-consuming and costly to manufacture.

SUMMARY OF THE INVENTION

It is an object of the invention, therefore, to provide
a simple smoking apparatus design that facilitates mass
production; to provide such a design which facilitates mass
30 production of a plurality of smoking apparatus body sections
from a single piece of wood in a simple milling operation;
to provide such a design which facilitates mass production
of smoking apparatus body sections and smoking apparatus
lids from a single piece of wood in a simple milling
35 operation; and to provide such a design which facilitates

production of smoking apparatuses using a multiple-head wood milling machine.

5 Briefly, therefore, the invention is directed to a compact wooden smoking apparatus comprising a smoking apparatus body having a body top, a body bottom, and body external side walls; wherein the body has a constant peripheral contour in cross sections taken in any plane generally parallel to the body top and body bottom; a smoking material receptacle in the body having a smoking material receptacle opening at the body top; and a lid for the smoking material receptacle, the lid having a lid top, a lid bottom, a lid width, lid depth, and lid external walls; wherein the lid has a constant peripheral contour in cross sections taken in any plane generally parallel to the lid top and lid bottom.

10 The invention is also directed to a compact wooden smoking apparatus comprising a smoking apparatus body having a body top, a body bottom, and body external side walls; wherein the body has a constant peripheral contour in cross sections taken in any plane generally parallel to the top and bottom of the body; a smoking material receptacle in the body having a smoking material receptacle opening at the body top; and a lid for the smoking material receptacle, the lid being pivotably attached to the body top.

20 In another aspect the invention is a wooden blank for use in the manufacture of a plurality of compact wooden smoking apparatuses, the wooden blank comprising an elongate piece of milled wood comprising a first end; a second end remote from the first end; a longitudinal axis extending from the first end to the second end; a plurality of smoking apparatus body sections disposed between the first end and the second end; and a constant peripheral contour in cross sections taken in any plane generally perpendicular to said longitudinal axis.

5 The invention also includes a method for manufacturing a compact wooden smoking apparatus comprising milling an elongate piece of wood into an elongate wooden blank imparting a constant peripheral contour in cross sections taken in any plane generally perpendicular to a longitudinal axis of the piece of wood; cutting lateral sections of a first length from the wooden blank to produce a plurality of smoking apparatus body sections; and boring a smoking material receptacle into each of said plurality of smoking apparatus body sections.

10 Other objects and features will be in part apparent and in part pointed out hereinafter.

BRIEF DESCRIPTION OF THE DRAWINGS

15 FIGS. 1, 4, and 7 are perspectives of fully assembled smoking apparatuses with pivotable lids in closed position.

FIGS. 3, 6, and 9 are perspectives of fully assembled smoking apparatuses with pivotable lids in open position.

20 FIGS. 2, 5, and 8 are perspectives of the main body component of smoking apparatuses of the invention without attached lids.

FIG. 10 is a perspective view of an embodiment of the invention with the lid in an open position with a pipe extending above the top edge of the body.

25 FIGS. 11 -13 are perspective views of milled wooden blanks of the invention.

FIG. 14 is a bottom view of a smoking apparatus body of the invention.

FIGS. 15 - 17 are top views of a smoking apparatus body of the invention.

30 FIG. 18 is a top view of a smoking apparatus of the invention with a lid attached to the smoking apparatus body and the lid rotated to an open position.

35 FIG. 19 is a front elevation of the smoking apparatus of the invention illustrating in phantom a hole for attachment of the lid to the smoking apparatus body.

FIG. 20 is a bottom view of smoking apparatus of claim 19.

FIG. 21 is a front elevation of the invention with the attachment hole, smoking material receptacle, and pipe receptacle and replacement lid shown in phantom.

FIG. 22 is a front elevation of the invention with the lid in an open position and a pipe extending above the top edge of the smoking apparatus body.

FIG. 23 is an exploded perspective view of the attachment screw, lid, and smoking apparatus body of the invention.

FIGS. 24 and 26 are perspective views of a prior art smoking apparatus.

FIG. 25 is a perspective view of a body portion of a prior art smoking apparatus.

FIG. 27 is a top view of a lid of a prior art smoking apparatus.

FIGS. 28 and 29 are top views of a prior art smoking apparatus with lid attached to body.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The compact smoking apparatus of the present invention can advantageously be manufactured using a multiple-head wood milling machine. Such machines are used, for example, by wood mills to manufacture linear feet of wooden trim pieces such as baseboards, window casings, and crown moldings. Here, a multiple-head wood milling machine simultaneously utilizes multiple sets of custom made steel cutting knives to transform linear feet of lumber into a milled section of wood having the desired external shape of the smoking apparatus body, and preferably the smoking

apparatus lid. The shape of the apparatus is therefore selected to be conducive to being shaped using a multiple-head wood milling machine having a shape which is constant throughout the entire length of the invention on both the body and the lid. This is to facilitate the capabilities of the wood milling machine, in that a multiple head wood milling machine mills a linear section of wood into a shape that is constant, i.e., such that the shape and contour of the resulting linear section do not change along a linear direction from one end of the section to the other end of the section.

One advantage of the process and product of the invention is speed of manufacturing. The machine can transform a twelve foot section of lumber into a shape capable of yielding, e.g., thirty to fifty smoking apparatus bodies in under a minute, or in even less time for high speed, state-of-the-art machines. Another advantage is the ease of applying early finish coats of paint or varnish, as it is easier to paint, for example, an eight foot linear section than to paint thirty-two individual three inch parts.

In one preferred embodiment, the smoking apparatus has a pivotably mounted lid consisting entirely of a shape that is formed using a multiple-head wood milling machine. Still more preferably, this lid has a profile corresponding to the profile of the smoking apparatus body, such that it is of a shape which is formed using the same machine as, at the same settings as, and formed simultaneously with the main body of the apparatus. In other words, the lid has an external

shape and contour which do not change along the linear direction from the top of the lid to the bottom of the lid. Because the shape of the lid is the same down its entire side, there are no additional wood-shaping processes required in creating the lid exterior side wall shape other than one milling operation. In the preferred embodiment where the profile of the lid corresponds to the profile of the main body of the apparatus, there are similarly no additional wood-shaping processes required to create the lid and body exterior side wall shapes other than the single milling operation to produce the lid and apparatus body side wall shapes. The reduction in the number of shaping operations required to produce the exterior side wall shapes of the lid and main body correspond to faster and less expensive production. Moreover, this shape permits simultaneous access to both the pipe and tobacco receptacles when the lid is rotated 90° to an open position.

FIGS. 1-9 are all perspective views of certain preferred embodiments of the invention, though they are by no means exhaustive of the embodiments of the invention. FIGS. 1, 4, and 7 are perspectives of fully assembled smoking apparatuses with pivotable lids in closed position. FIGS. 3, 6, and 9 are perspectives of fully assembled smoking apparatuses with pivotable lids in open position. FIGS. 2, 5, and 8 are perspectives of the body components of smoking apparatuses of the invention without attached lids. As pointed out in FIGS. 1-3 and evident from examination of the other figures, the relieves, or contours located on the exterior side wall surfaces 6 and 7 extend the entire length

of both the lid and the body. The external shape of each embodiment of the invention is constant from the top surface of the lid to the bottom surface of the body. This feature facilitates simple single-pass manufacture using a multiple-head wood milling machine on a length of wood to be sectioned into a large number of smoking apparatuses. The body and lid each have a constant peripheral contour in cross sections taken in any plane generally parallel to the top and bottom of each. By "generally parallel," it is encompassed that if the top of each is not parallel to the bottom of each, the planes from which the cross sections are taken are generally parallel to, for example, an average of the top and bottom. Stated another way, the external side walls of each of the lid and body do not change in a linear direction from the top of each to the bottom of each. And still another way, there is a constant peripheral contour in cross sections taken in any plane generally perpendicular to a centerline or longitudinal axis from the top of each to the bottom of each.

FIG. 11 shows a wooden blank of the invention after being milled with a multiple-head wood milling machine into a shape that will be sectioned into several units of the body and lid of the smoking apparatus. The wooden blank is milled from a generally rectangular or other-shaped length of wood and is elongate in that it has a lengthwise dimension which is substantially larger than its width and depth. After the wood is milled into this wooden blank, in one preferred embodiment, bodies 1 and lids 2 are cut to length from the same blank as illustrated by the dashed

lines in FIG. 11. FIGS. 12 and 13 illustrate alternative embodiments from which the apparatus of FIGS. 4 and 7 are sectioned.

FIG. 11 illustrates bodies and lids cut in alternating fashion from one piece of wood. This preferred embodiment has the added aesthetic advantage that in the finished product the wood grain in the lid matches up to the wood grain in the body. Alternatively, the lids and bodies are cut from completely different pieces of wood. Further alternatively, the lids and bodies are cut from the same piece of wood, but not necessarily in the alternating fashion shown in FIG. 11; for example, the lids are all cut from one end of the blank and the bodies are all cut from another end of the blank.

It is seen from these illustrations, therefore, that in one aspect the invention is a wooden blank for use in the manufacture of a plurality of compact wooden smoking apparatuses. The wooden blank comprises an elongate piece of milled wood having a first end, a second end remote from the first end, side walls having a shape and a contour which do not change along a linear direction from the first end to the second end, a plurality of smoking apparatus body sections of a first length disposed between the first end and the second end, and a plurality of smoking apparatus lid sections of a second length disposed between the first end and the second end. In other words, the blank has an constant peripheral contour in cross sections taken in any plane generally perpendicular to the longitudinal axis of the piece of wood. The second length is shorter than the

first length. It is also seen that in one embodiment the body sections and lid sections are disposed alternatively along the wooden blank such that each of at least a plurality of the body sections are adjacent to lid sections.

5 In one preferred embodiment, the external side wall shape of the lid, which corresponds to the external side wall shape of the body, allows the full diameter of both the smoking material receptacle and pipe receptacle to be simultaneously exposed when the pivotably mounted lid is rotated ninety degrees in relation to the body to an open position. This is the reason for the contours on the front and back surfaces on both the body and the lid 6 and 7 of the smoking apparatus. While these contours are not necessary on the body, the capabilities of a multiple-head wood milling machine dictate that an elongate section of
10 lumber be milled into the same constant shape. The contours on the front and back surfaces also serve ergonomic and aesthetic purposes.

15 Some secondary drilling operations are performed after cutting the linear feet into lengths approximating the desired height of a single body. In particular, receptacles for smoking material and a pipe are bored into the body as indicated at the openings 3 and 4 in FIG. 15, and as is known from U.S. Pat. Nos. 4,214,658; 5,465,738; and
20 5,810,164. The smoking material receptacle is preferably greater in diameter, and shorter in length, as compared to the pipe receptacle. The pipe receptacle also houses a spring near the bottom of the receptacle. A spring upwardly biases the top edge of the pipe above the top edge of the
25

body 1 when the lid, which serves as closure for the pipe and smoking material receptacles, is moved to open position.

FIG. 16 illustrates that in a preferred embodiment the distance (A) between the smoking material receptacle opening and the pipe receptacle opening in the body is greater than depth (B) of the body and the like depth of the lid at the pivot point. If B were greater than A, portions of the smoking material receptacle opening 3 and the pipe receptacle opening 4 would still be covered when the lid is rotated ninety degrees to an open position. It is seen, therefore, that the pipe receptacle opening is a distance from the smoking material receptacle opening, which distance is greater than the lid depth. This feature provides unobstructed access to the smoking material receptacle opening and pipe receptacle opening upon rotation of the lid to an open position.

FIGS. 14-18 illustrate how the external shape of a single end product is dictated by both the secondary procedures needed to make a single product as well as the criteria that must be met allowing a design wherein the lid 2 and the body 1 have an identical external shape capable of being manufactured using a multiple-head wood milling machine. FIG. 15 shows the body 2 must be of sufficient size to contain the full diameters of both the smoking material receptacle opening 3 and the pipe receptacle opening 4. Another cavity in the body is simply a pilot hole 5 to facilitate attachment of a pivotably mounted lid. The pilot

hole on the top surface of the body 5 is located between the two contours on the front and back surfaces of the body 6 and 7.

FIG. 18 is a top view of the invention with the lid 2 rotated ninety degrees to an open position. The lid is pivotably mounted in this particular embodiment by means of a pan head washer type screw 8. The shape of the lid 2, which is identical to the shape of the body 1, allows the full diameter of both the smoking material receptacle opening 3 and the pipe receptacle opening 4 to be exposed when rotated to an open position. To further ensure that full diameters of the openings in the body are exposed when the lid is rotated to an open position, in this embodiment the radius of the external side wall contours is greater than the radius of the smoking material receptacle opening as illustrated in FIG. 17. Accordingly, the smoking apparatus side walls have a generally arcuate contour having a contour radius dimension R1. The smoking material receptacle opening is circular, oval, or of another shape which has an arcuate section at a point on the opening closest to a center point of the smoking apparatus body. There is a smoking material receptacle radius dimension R2 corresponding to this arcuate section. The contour radius dimension R1 is greater than the smoking material receptacle dimension R2.

Since both the body and the lid are milled from linear feet of lumber, the natural wood grain runs vertically through both the body and the lid. This means that the end grain of the wood is exposed on both the top and bottom

surfaces of both the body and the lid. This is not a problem on the noticeably larger section that comprises the body. The lid, however, with the end grain exposed on the top and bottom surfaces, has less strength than another lid of identical thickness where the natural wood grain is parallel to the front and back of the surface of the lid. The lid proposed in this invention is roughly the same thickness as others on the market.

Concerns with regard to structural strength of the lid, therefore, are addressed in one aspect by selection of the type of fastener that attaches the lid to the body at the pivot point. Generally, prior smoking apparatuses having a pivotally mounted lid use either a countersunk flathead screw or a countersunk socket head cap screw. However, the structurally weakest section of the lid is the location of the pivot point at the lid. Removing extra wood for a countersunk screw on the top of the lid at the pivot point only makes the lid more fragile. This invention, therefore, uses a different type of fastener that does not require a countersunk hole, so less wood is removed from the weakest part of the lid. This decreases the likelihood of the lid breaking during usage. One preferred fastener is a pan head washer type screw. This type of screw offers two specific advantages for this application. There is no need to countersink the screw, leaving more wood material at the weakest part of the lid. Also, the pan head washer type of screw gets its name from the integrated washer on the underside of the screw head. This integrated washer allows the fastener to exert downward pressure more evenly across

the top of the lid, allowing a tighter seal between the body and the lid when the lid is covering the openings in the body. By utilizing a fastener wherein the bottom surface of the head of the fastener contacts the top of the surface of the lid, there is no need for a countersunk hole. Only a small pilot hole 35 is required leaving more material as part of the lid bolstering the structural integrity of the weakest part of the lid as shown in FIGS. 19 and 20.

A second optional aspect of the invention to strengthen the structural integrity of the lid is a thin metal plate adhered to the lid. In one embodiment of the invention the metal plate is adhered to the underside of the lid and covers the openings in the body when the lid is in the closed position.

As is seen in FIG. 21 there is a section at the bottom of the apparatus body below the bottom of both of the bores for the smoking material receptacle and pipe receptacle, indicated in FIG. 21 as below the horizontal phantom line. In a further variation on the above-described embodiments, the body is made sufficiently long to provide for a replacement lid section in the event the original lid is lost or broken. This may be preformed and attached to the bottom of the body, or the user can simply be provided instructions on cutting off a section of the bottom to create a replacement lid should the need arise. The constant shape of the body and lid permits attachment of the replacement lid to the bottom of the body. This is a significant advantage of having the lid, replacement lid, and body external side walls have a shape and contour which

do not change along a linear direction from the top of each to the bottom of each, and to having these respective components alignable such that there is no such change among them. There is therefore optionally a replacement lid section extending upwardly from the smoking apparatus body bottom.

From the foregoing description it is seen that in one aspect the invention is a method for manufacturing a compact wooden smoking apparatus. The method involves milling an elongate piece of wood to impart a shape and a contour which do not change along a linear direction from a first end of the piece of wood to a second end of the piece of wood, thereby yielding a wooden blank for further processing. In one embodiment the contour(s) has a uniform depth and uniform width and is formed by the removal of wood and extends from the top of the lid to the bottom of the body bottom. One particular preferred method involves milling to provide a contour having a generally arcuate shape as shown in FIGS. 11 and 13. Then lateral sections of a first length are cut from the wooden blank to produce a plurality of smoking apparatus body sections. A smoking material receptacle is bored into each of the plurality of smoking apparatus body sections. A lid is fastened to each of the plurality of smoking apparatus sections to provide a smoking material receptacle closure for each of the plurality of smoking apparatus body sections. In a preferred embodiment lateral sections of a second, shorter length are cut from the elongate piece of wood to produce the smoking apparatus lids.

The foregoing relates only to a limited number of embodiments that have been provided for illustration purposes only. It is intended that the scope of invention is defined by the appended claims and there are modifications of the above embodiments that do not depart from the scope of the invention.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2